


Luminaire
Code KUSHI FLOOR LED
Name KUSHI FLOOR LED
Measurerm.
Code 0001FT20S
Name KUSHI FLOOR LED

Luminaire Flux	458.00 lm	Luminaire Power	4.60 W	Efficacy	99.57 lm/W	Efficiency	100.00%
Sources Flux	458.00 lm	Maximum value	92.86 cd/klm	Position	C=0.00 G=174.00	CG	Rotosymmetrical
Round Luminaire		Diam.	160 mm	Height	180 mm		
Round Luminous Area		Diam.	160 mm	Height	120 mm		
Horizontal Luminous Area		0.020106 m2		Emitting area on Plane 180°		0.019200 m2	
Emitting area on Plane 0°		0.019200 m2		Emitting area on Plane 270°		0.019200 m2	
Emitting area on Plane 90°		0.019200 m2		Glare area at 76°		0.023494 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		01-05-2020		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		458.00 lm	

Luminaire Sources					Flux [lm]	Pow. [W]	Q.ty
Line	Board LED SMD - 700mA - 4W - Nominal Lumen 650 lm - 2700K - CRI80				458.00	4.60	1
C.I.E.	22	47	73	45	100		
F UTE	0.45	J	0.55	T			
					D DIN 5040	C12	
					B NBN	BZ 9 / 2.5 / BZ 8 / 3 / BZ 9	

Diam=160mm



C Halfplanes

180.0 — 0.0

ULOR 54.77 %
DLOR 45.23 %
RN 54.77 %

